

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000

Cerca

Star

Calendar

Mail

Download

Home

Location

ABP

Refresh

Search

Printer

More

MyPBX

Status

System

PBX

Reports

Addons

Logout

Network Preferences

LAN Settings

WAN Settings

DHCP Server

VLAN Settings

VPN Settings

DDNS Settings

Static Route

Security Settings

Security Center

Firewall Rules

IP Blacklist

AMI Settings

Database Grant

Alert Settings

LDAP Server

Storage Management

System Preferences

General Preferences

General Settings

Note:
It is strongly recommended to add local network address to a common rule with the 'action' is 'accept', or it may be dragged into the blacklist.

☒ Enable Firewall

☐ Disable Ping

☐ Drop All

Common Rules

+ Add Rule

Action	Name	Protocol	IP	MAC Address	Port		
ACCEPT	Lan_interna	BOTH	192.168.1.0/255.255.255.0	--	1:65535		

Auto Defense

+ Add Rule

No Auto Defense Rules Defined

Save

Cancel

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000Cerca

MyPBX

StatusSystemPBXReportsAddonsLogout

Network Preferences

LAN Settings

WAN Settings

DHCP Server

VLAN Settings

VPN Settings

DDNS Settings

Static Route

Security Settings

Security Center

Firewall Rules

IP Blacklist

AMI Settings

Database Grant

Alert Settings

LDAP Server

Storage Management

System Preferences

IP Blacklist

Blacklist Rules

Add Rule

Port	Protocol	Rate		
5060	UDP	120/60s		
5060	UDP	40/2s		
8022	TCP	5/60s		

IP Blacklist

Delete the selected Blacklist

Total: 0Show: 0View: 25

No Auto Black IP Address

<<PrevNext>>Page : 0 / 0Goto

Static Route Settings

Static Route

Alert Settings

▶ **System Preferences**

Destination	Subnet Mask	Gateway	Metric	Interface
192.168.1.0	255.255.255.0	0.0.0.0	0	LAN
224.0.0.0	224.0.0.0	0.0.0.0	0	LAN
0.0.0.0	0.0.0.0	192.168.1.1	0	LAN

Destination: Subnet Mask: Gateway: Metric: Interface: LAN Add

No Static Routes Defined

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000

Cerca

FXS/VoIP Extensions

Phone Provisioning

TA Provisioning

Trunks

Physical Trunk

VoIP Trunk

Outbound Call Control

Outbound Routes

Speed Dial Settings

Inbound Call Control

IVR

Ring Groups

Queues

Conferences

Inbound Routes

Audio Settings

Basic Settings

General Preferences

Business Hours

Feature Codes

Voicemail Settings

Advanced Settings

SIP Settings

IAX Settings

Blacklist

Callback Settings

DNIS Settings

BRI Trunk

Trunk Name	Port
BriTrunk3	3

Edit BRI Trunk - BriTrunk3

Analog Trunk

GSM/UMTS Trunk

Trunk Name: BriTrunk3

Signaling: BRI-CPE

Overlap Dial: no

PRI Indication: Inband

Nsf: none

Hide Caller ID: No

Switch Type: euroisdn

Reset Interval: never

Enable Facility: Enabled

Echo Cancellation: On

Codec: alaw

Caller ID Prefix

ISDN Dialplan: Yes

International Prefix: 00

Local Prefix: 0

Unknown Prefix:

National Prefix: 0

Private Prefix: 0

Dialplan

Remote Dialplan: unknown

Remote Number Type: unknown

Location Dialplan: unknown

Location Number Type: unknown

DOD Settings

Global DOD:

DOD: Associated Extension: 601

Add DODAdd Bulk

SaveCancel

- ## DNIS Settings

The screenshot shows the Asterisk Manager GUI with a table of routes. A dialog box titled "Edit Outbound Route - pstnout" is open, allowing configuration of the "pstnout" route. The dialog includes fields for "Route Name" (set to "pstnout"), "Password" (a dropdown menu), and "T.38 Support" (set to "No"). A link for "PIN Settings" is also present.

Edit Outbound Route - pstnout

Route Name:

Password: [PIN Settings](#)

T.38 Support:

Rmemory Hunt:

Time Groups:

Dial Patterns

Dial Pattern	Strip	Prepend
X.		

 Add 

Member Extensions

Available Extensions		Selected
13(SIP) 14(SIP) 15(SIP)	»» → ← ««	10(SIP) 11(SIP) 12(SIP) 601(FXS) 111(SIP) 112(SIP) 113(SIP) 114(SIP)

Member Trunks

Available Trunks		Selected
Skype(SIP)	»» → ← ««	BriTrunk4(BRI) BriTrunk3(BRI) pstn2(FXO)

 Save  Cancel

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000

Cerca

FXS/VoIP Extensions

Phone Provisioning

TA Provisioning

Trunks

Physical Trunk

VoIP Trunk

Outbound Call Control

Outbound Routes

Speed Dial Settings

Inbound Call Control

IVR

Ring Groups

Queues

Conferences

Inbound Routes

Audio Settings

Basic Settings

General Preferences

Business Hours

Feature Codes

Voicemail Settings

Advanced Settings

SIP Settings

IAX Settings

Blacklist

Callback Settings

DNIS Settings

+Add Inbound Route

✖Delete the selected Route

Edit Inbound Route: Fax

General

Route Name: Fax

DID Number: 298126770

Extension:

Caller ID Number:

Distinctive Ringtone:

Enable Callback: No

Callback Settings

Member Trunks

Available Trunks

pstn2(FXO)

BriTrunk4(BRI)

Skype(SIP)

Selected

BriTrunk3(BRI)

Time Conditions

Time Groups: default

Day Destination: Faxes

Faxes -- 601

Night Destination: Faxes

Faxes -- 601

During Holidays

Holiday:

Destination: End Call

Fax Detection

Destination: No Detect

Save

Cancel

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000

Cerca

FXS/VoIP Extensions

Phone Provisioning

TA Provisioning

Trunks

Physical Trunk

VoIP Trunk

Outbound Call Control

Outbound Routes

Speed Dial Settings

Inbound Call Control

IVR

Ring Groups

Queues

Conferences

Inbound Routes

Audio Settings

Basic Settings

General Preferences

Business Hours

Feature Codes

Voicemail Settings

Advanced Settings

SIP Settings

IAX Settings

Blacklist

Callback Settings

DNIS Settings

Add Inbound RouteDelete the selected Route

Edit Inbound Route: pstnin

General

Route Name: pstnin

DID Number:

Extension:

Caller ID Number:

Distinctive Ringtone: esterna

Enable Callback: No

Callback Settings

Member Trunks

Available Trunks

Skype(SIP)

Selected

BriTrunk3(BRI)
BriTrunk4(BRI)
pstn2(FXO)

Time Conditions

Time Groups: default

Day Destination: Ring Group

Ring Group -- SDSGiorno

Night Destination: Ring Group

Ring Group -- SDSGiorno

During Holidays

Holiday:

Destination: Voicemail

Voicemail -- 10

Fax Detection

Destination: Faxes

Faxes -- 601

Save

Cancel

SIP Settings

TA Provisioning

Physical Trunk

VoIP Trunk

Outbound Routes

Speed Dial Settings

IVR

Ring Groups

Queues

Conferences

Inbound Routes

Basic Settings

General Preferences

Business Hours

Feature Codes

Voicemail Settings

SIP Settings

ed Settings

UDP Port : 5060

☐ Enable TCP Port : 5060

☐ Enable TLS Port : 5061

TLS Verify Server : No 

TLS Verify Client : No

TLS Ignore Common Name : Yes 

TLS Client Method:

RTP Port Start: 10005

RTP Port End: 12000

DTMF Mode ⓘ: rfc2833 ▾

Max Registration/Subscription Time ⓘ: 3600

Min Registration/Subscription Time ⓘ: 60

Default Incoming/Outgoing Registration Time ⓘ: 120

Register Attempts : 0

Register Timeout ⓘ: 20

Calling Channel Codec Priority: Yes

Video Support : Yes 

Max Bit Rate ⓘ: 384 kb/s

DNS SRV Look Up :

User Agent :

Enable 100rel:

Save

 Cancel

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000

Cerca

MyPBX

StatusSystemPBXReportsAddonsLogout

Extensions

FXS/VoIP Extensions

Phone Provisioning

TA Provisioning

Trunks

Physical Trunk

VoIP Trunk

Outbound Call Control

Outbound Routes

Speed Dial Settings

Inbound Call Control

IVR

Ring Groups

Queues

Conferences

Inbound Routes

Audio Settings

Basic Settings

General Preferences

Business Hours

Feature Codes

Voicemail Settings

Advanced Settings

SIP Settings

IAX Settings

Voicemail Settings

General Voicemail Settings

Message Options

Max Messages per Folder: 100

Max Message Time: 5 Minutes

Min Message Time: 5 Seconds

Ask Caller to Dial 5:

Delete Voicemail:

Operator Breakout from Voicemail: No

Destination: welcome

Greeting Settings

Busy Prompt: Play busy greeting

Unavailable Prompt: Play unavailable greetings

Leave a Message Prompt: Skip greeting

Playback Options

Announce Message Caller ID:

Announce Message Duration:

Announce Message Arrival Time:

Allow Users to Review Messages:

SMTP Settings For Voicemail

Note: If you would like to send voicemail messages as email attachments, please configure this section.

SMTP Settings

E-mail Address: pbxsds@sdsitalia.it

Password:

SMTP Server: smtp.tiscali.it

Port: 25

Use TLS to send secure message to server

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000

Cerca

MyPBX

StatusSystemPBXReportsAddonsLogout

Extensions

FXS/VoIP Extensions

Phone Provisioning

TA Provisioning

Trunks

Physical Trunk

VoIP Trunk

Outbound Call Control

Outbound Routes

Speed Dial Settings

Inbound Call Control

IVR

Ring Groups

Queues

Conferences

Inbound Routes

Audio Settings

Basic Settings

General Preferences

Business Hours

Feature Codes

Voicemail Settings

Advanced Settings

SIP Settings

FXS/VoIP Extensions

FXS Extensions

Port	Extension
1	60

VoIP Extensions

Add Extension

Add

Extension
☐ 10
☐ 11
☐ 12
☐ 13
☐ 14
☐ 15
☐ 16
☐ 111
☐ 112
☐ 113
☐ 114
☐ 115
☐ 200

Edit Extension - Silvio

General

Other Settings

General

Type: SIP

Extension: 10

Password: sdsmax01

Name: Silvio

Caller ID: 10

Register Name: 10

Voicemail

☒ Enable Voicemail

Voicemail Access PIN #: 10

Mail Setting

☐ Enable Send Voicemail

Email Address: dezza@sdsitalia.it

Note: Please ensure that the section 'SMTP Settings for Voicemail'(in the 'Voicemail Settings') have been properly configured before using this feature.

Group

Pickup Group: 1

Call Duration Setting

Max Call Duration: s

VoIP Settings

NAT: ☐

Qualify: ☒

Enable SRTP: ☐

Transport: UDP

DTMF Mode: RFC2833

Register Remotely: ☐

Save

Cancel

Next >

Last >>

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000

Cerca

MyPBX

StatusSystemPBXReportsAddonsLogout

Extensions

FXS/VoIP Extensions

Phone Provisioning

TA Provisioning

Trunks

Physical Trunk

VoIP Trunk

Outbound Call Control

Outbound Routes

Speed Dial Settings

Inbound Call Control

IVR

Ring Groups

Queues

Conferences

Inbound Routes

Audio Settings

Basic Settings

General Preferences

Business Hours

Feature Codes

Voicemail Settings

Advanced Settings

SIP Settings

Phone Provisioning

General Settings for Yealink

General Settings for Aastra

Phone Book

Configured Phone

Not Configured Phone

Add Phone

Add B

ID	MAC Address
☐ 1	000B8248C66A
☐ 2	0015654D6CE
☐ 3	0015654D6E3
☐ 4	0015654E9299
☐ 5	0015654E936D
☐ 6	0015654E9449
☐ 7	001565822D20

Configure the selected Ph

Upload a file

No Files Found.

Edit Yealink Phone

General

Codecs

Line Keys Settings

Enabled: Yes

NewConfig: Yes

MAC Address: 0015654e9299

Name: Silvio

Manufacturer: Yealink

Phone Type: T42

Call Waiting: Enabled

Key As Send: #

Auto Redial: Disabled

Auto Answer: Disabled

Phone Book: Enabled

Line

☒ Line1

Extension: 10

Label: 10

Line Active: ☒

☐ Line2

Extension:

Label:

Line Active: ☐

☐ Line3

Extension:

Label:

Line Active: ☐

Save

Cancel

Show: 1-7

View: 15

Show: 0-0

View: 15

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...

192.168.1.150:82/cgi/WebCGI?1000

Cerca

MyPBX

StatusSystemPBXReportsAddonsLogout

Extensions

FXS/VoIP Extensions

Phone Provisioning

TA Provisioning

Trunks

Physical Trunk

VoIP Trunk

Outbound Call Control

Outbound Routes

Speed Dial Settings

Inbound Call Control

IVR

Ring Groups

Queues

Conferences

Inbound Routes

Audio Settings

Basic Settings

General Preferences

Business Hours

Feature Codes

Voicemail Settings

Advanced Settings

SIP Settings

Phone Provisioning

General Settings for Yealink

General Settings for Aastra

Phone Book

Configured Phone

Add Phone

Add B

ID	MAC Address
1	000B8248C66A
2	0015654D6CE
3	0015654D6E3
4	0015654E9299
5	0015654E936D
6	0015654E9449
7	001565822D20

Not Configured Phone

Configure the selected Ph

Upload a file

No Files Found.

Edit Yealink Phone

GeneralCodecsLine Keys Settings

Line Keys Settings

Line Key 1 - 10Line Key 11 - 15

Key	Type	Value	Label	Line	Extension
☒ Line Key 1	Speed Dial	3382654663	Nuccia_cell	line1	
☒ Line Key 2	Speed Dial	3341135324	Tecnico_cell	line1	
☒ Line Key 3	Speed Dial	00298230758	Casa	line1	
☒ Line Key 4	Intercom	11	Nuccia	line1	
☒ Line Key 5	Intercom	12	Valentina	line1	
☒ Line Key 6	Intercom	13	Carlo	line1	
☐ Line Key 7	N/A			Line1	
☐ Line Key 8	N/A			Line1	
☐ Line Key 9	N/A			Line1	
☐ Line Key 10	N/A			Line1	

SaveCancel

Show: 1-7View: 15

< Prev1Next >

Show: 0-0View: 15

FileModificaVisualizzaCronologiaSegnalibriStrumentiAiuto

MyPBX-Hybrid IP PBX for ...Yealink T42G PhoneYealink Support

192.168.1.151/servlet?p=account-register&q=load&acc=0Cerca

Logout

YealinkT42G

StatocontoNetworkTasto DSSFunzionaliImpostazioniRubricaSicurezza

Registra

di base

Codec

Avanzato

conto

conto 1

Stato registrazioneRegistrato

Account AttivoAbilitato

Etichetta10

Nome DisplaySilvio

Nome Register10

User Name10

Password

SIP Server 1

Server Host192.168.1.150Porta5060

trasportoUDP

Server Scade300

Conteggio tentativi server3

SIP Server 2

Server HostPorta5060

trasportoUDP

Server Scade3600

Conteggio tentativi server3

Abilita Outbound Proxy ServerDisabilitato

Outbound Proxy Server 1Porta5060

Outbound Proxy Server 2Porta5060

Proxy Fallback Interval3600

NAT TraversalDisabilitato

Conferma

Cancella

NOTA

Display Name
Il nome del subscriber del servizio SIP che verrà utilizzato per mostrare il CallerID

Register Name
L'ID subscriber del servizio SIP utilizzato per l'autenticazione

User Name
Account Utente, fornito dal service provider VoIP

NAT Traversal
Definisce se lo STUN server sarà attivo o no

You can click here to get more guides.

Copyright © 1998-2016 **Inc. All Rights Reserved